

Pump Performance Datasheet

Customer :	Quote Number / ID :	1471203
Customer ref. / PO :	Model :	25957 LC
Tag Number : 001	Stages :	1
Service :	Based on curve number :	RC9867-1-SS Rev 0
Quantity : 1	Basic model number :	-
	Date last saved :	09/19/2023 3:07 PM

Operating Conditions		Liquid	
Flow, rated	: 179.4 USgpm	Liquid type	: Cold Water
Differential head / pressure, rated (requested)	: 40.69 ft	Additional liquid description	:
Differential head / pressure, rated (actual)	: 40.69 ft	Solids diameter, max	: 0.00 in
Suction pressure, rated / max	: 0.00 / 0.00 psi.g	Solids concentration, by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 68.00 deg F
Site Supply Frequency	: 60 Hz	Fluid density, rated / max	: 1.000 / 1.000 SG

Performance		Material	
Speed, rated	: 1775 rpm	Material selected	: Cast iron
Impeller diameter, rated	: 6.87 in		
Impeller diameter, maximum	: 9.60 in		
Impeller diameter, minimum	: 6.50 in		
Efficiency	: 73.74 %		

Performance		Pressure Data	
NPSH required / margin required	: 2.57 / 0.00 ft	Maximum working pressure	: 21.04 psi.g
nq (imp. eye flow) / S (imp. eye flow)	: 21 / 140 Metric units	Maximum allowable working pressure	: 175.0 psi.g
MCSF	: 52.98 USgpm	Maximum allowable suction pressure	: 175.0 psi.g
Head, maximum, rated diameter	: 48.62 ft	Hydrostatic test pressure	: 263.0 psi.g
Head rise to shutoff	: 18.20 %		
Flow, best eff. point	: 179.4 USgpm		
Flow ratio, rated / BEP	: 100.00 %		
Diameter ratio (rated / max)	: 71.56 %		
Head ratio (rated dia / max dia)	: 41.88 %		
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00		
Selection status	: Acceptable		

Energy Indexes		Driver & Power Data (@Max density)	
PEI (CL)	: 0.92	Motor sizing specification	: Max power (non-overloading)
ER (CL)	: 8	Margin over specification	: 0.00 %
		Service factor	: 1.00
		Power, hydraulic	: 1.84 hp
		Rated power (based on duty point)	: 2.50 hp
		Max power (non-overloading)	: 2.99 hp
		Nameplate motor rating	: 3.00 hp / 2.24 kW

