

Pump Performance Datasheet

Customer :	Quote Number / ID :	1471203
Customer ref. / PO :	Model :	30127 LC
Tag Number : 001	Stages :	1
Service :	Based on curve number :	RC9873-2 Rev 1
Quantity : 1	Basic model number :	-
	Date last saved :	09/18/2023 5:31 PM

Operating Conditions		Liquid	
Flow, rated	: 522.3 USgpm	Liquid type	: Cold Water
Differential head / pressure, rated (requested)	: 130.3 ft	Additional liquid description	:
Differential head / pressure, rated (actual)	: 130.3 ft	Solids diameter, max	: 0.00 in
Suction pressure, rated / max	: 0.00 / 0.00 psi.g	Solids concentration, by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 68.00 deg F
Site Supply Frequency	: 60 Hz	Fluid density, rated / max	: 1.000 / 1.000 SG

Performance		Material	
Speed, rated	: 1760 rpm	Material selected	: Cast iron
Impeller diameter, rated	: 11.42 in		
Impeller diameter, maximum	: 12.10 in		
Impeller diameter, minimum	: 9.50 in		

Performance		Pressure Data	
Efficiency	: 78.77 %	Maximum working pressure	: 63.26 psi.g
NPSH required / margin required	: 16.64 / 0.00 ft	Maximum allowable working pressure	: 175.0 psi.g
nq (imp. eye flow) / S (imp. eye flow)	: 19 / 93 Metric units	Maximum allowable suction pressure	: 175.0 psi.g
MCSF	: 150.0 USgpm	Hydrostatic test pressure	: 263.0 psi.g
Head, maximum, rated diameter	: 146.2 ft		
Head rise to shutoff	: 12.19 %		

Performance		Driver & Power Data (@Max density)	
Flow, best eff. point	: 522.3 USgpm	Motor sizing specification	: Max power (non-overloading)
Flow ratio, rated / BEP	: 100.00 %	Margin over specification	: 0.00 %
Diameter ratio (rated / max)	: 94.38 %	Service factor	: 1.00
Head ratio (rated dia / max dia)	: 87.94 %	Power, hydraulic	: 17.18 hp
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00	Rated power (based on duty point)	: 21.81 hp
Selection status	: Acceptable	Max power (non-overloading)	: 24.99 hp
		Nameplate motor rating	: 25.00 hp / 18.64 kW

Energy Indexes	
PEI (CL)	: 0.97
ER (CL)	: 3

