

Pump Performance Datasheet

Customer :	Quote Number / ID :	1471203
Customer ref. / PO :	Model :	25953 VL
Tag Number : 001	Stages :	1
Service :	Based on curve number :	VL_25953_2P Rev Aug21
Quantity : 1	Basic model number :	-
	Date last saved :	11/03/2023 6:04 PM


Operating Conditions	Liquid
Flow, rated : 436.7 USgpm	Liquid type : Cold Water
Differential head / pressure, rated (requested) : 287.4 ft	Additional liquid description :
Differential head / pressure, rated (actual) : 288.2 ft	Solids diameter, max : 0.00 in
Suction pressure, rated / max : 0.00 / 0.00 psi.g	Solids concentration, by volume : 0.00 %
NPSH available, rated : Ample	Temperature, max : 68.00 deg F
Site Supply Frequency : 60 Hz	Fluid density, rated / max : 1.000 / 1.000 SG

Performance	Material
Speed, rated : 3550 rpm	Material selected : Ductile iron
Impeller diameter, rated : 9.41 in	
Impeller diameter, maximum : 9.60 in	
Impeller diameter, minimum : 7.00 in	
Efficiency : 70.07 %	
NPSH required / margin required : 64.10 / 0.00 ft	
nq (imp. eye flow) / S (imp. eye flow) : 20 / 62 Metric units	
MCSF : 131.0 USgpm	
Head, maximum, rated diameter : 359.1 ft	
Head rise to shutoff : 23.63 %	
Flow, best eff. point : 436.7 USgpm	
Flow ratio, rated / BEP : 99.99 %	
Diameter ratio (rated / max) : 98.02 %	
Head ratio (rated dia / max dia) : 94.31 %	
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010] : 1.00 / 1.00 / 1.00 / 1.00	
Selection status : Acceptable	

Pressure Data
Maximum working pressure : 155.4 psi.g
Maximum allowable working pressure : 400.0 psi.g
Maximum allowable suction pressure : 400.0 psi.g
Hydrostatic test pressure : 600.0 psi.g

Driver & Power Data (@Max density)
Motor sizing specification : Max power (non-overloading)
Margin over specification : 0.00 %
Service factor : 1.00
Power, hydraulic : 31.68 hp
Rated power (based on duty point) : 45.21 hp
Max power (non-overloading) : 49.68 hp
Nameplate motor rating : 50.00 hp / 37.29 kW

Energy Indexes
PEI (CL) : 0.94
ER (CL) : 6



Grundfos Series VL - In-Line Centrifugal Pump, Close Coupled


QUOTE NUMBER / ID 1471203	UNIT TAG 001	QUANTITY 1
REPRESENTATIVE	SERVICE	
ENGINEER	SUBMITTED BY	DATE
CONTRACTOR	APPROVED BY	DATE
	ORDER #	DATE



VL 25953
3550 rpm

Part Number N/A

Conditions of Service		Pump Data		Motor Data	
Flow	436.7 USgpm	Impeller Diameter	9.40 in	Motor HP	50 HP
Head	287.4 ft	Max. Imp. Dia.	9.60 in	BHP	45.21 HP
Liquid	Cold Water	Min. Imp. Dia.	7.00 in	Enclosure	TEFC
Temperature	68.00 deg F	Efficiency	70.07 %	Voltage	230/460 V
NPSHr	64.10 ft	Suction	-1 in.	Phase	3 Phase
Viscosity	1.00 cP	Discharge	-1 in.	Cycle	60
Specific Gravity	1.000 SG	PEI (CL)	0.94	Frame Size	
		ER (CL)	6		





QUOTE NUMBER / ID 1471203

UNIT TAG 001

VL 25953

Grundfos Series VL - In-Line Centrifugal Pump, Close Coupled

NOT FOR CONSTRUCTION, unless certified and referenced on order

Units	Frame	S x D	AG (Max)	DC	DD	DE	E	P (Max)	X	YY	Weight
inches			-1.00	-1.00	-1.00	-1.00	-1.00	-1.00	-1.00	-1.00	TBD